

# **Technical Data Sheet** SCHQ30

 Doc. number
 Issue

 542 400 057
 01

## Description of the material

SCHQ30 is a mineral casting mixture consisting of a basis of epoxy resin and a high amount of quartzitebased stone. It has good processing properties when utilised in conjunction with cold casting methods. When used, it is durable, non-corrosive, chemically inert, resists most chemicals, and can be disposed of at a conventional waste facility.

#### **Characteristics**

- High rigidity
- Good damping characteristics
- Low thermal conductivity
- Lower component thicknesses

### **Material properties**

- Density
- Modulus of elasticity
- Compressive strength
- Tensile strength
- Poisson's ratio
- Damping ratio
- Therm. expansion coefficient
- Heat conductivity
- Spec. thermal capacity
- Linear shrinkage
- Component thickness
- Maximum grain size

- typ. 2.30 kg/dm<sup>3</sup>
- typ. 40 kN/mm<sup>2</sup> (35-40 kN/mm<sup>2</sup>) typ. 110 N/mm<sup>2</sup> (>80 N/mm<sup>2</sup>)
- typ. 15 N/mm<sup>2</sup> (>12 N/mm<sup>2</sup>)
- typ. 0.2
- typ. 0.2
- typ. 19\*10<sup></sup> K<sup>-1</sup> at 20°C
- typ. 3 W/m K at 20°C
- typ. 0.9 kJ/kg K at 20°C
- typ. 0.3 mm/meter
- typ. 60 mm
- typ. 12 mm

### Area of application

Universal casting mixture with good damping characteristics suitable for easily refillable machine components with high requirements regarding rigidity. It is also suitable to be used for filling welded steel constructions, grey cast iron and other components.

### Comment

The material recommendations are based on the experience of many years and correspond to the present state of knowledge. Suitability tests are the responsibility of the customer and cannot not be assumed by the vendor.

### Material qualification

The material properties were compiled in co-operation with inspire AG and institutes of the ETH Zurich and the examinations were carried out by authorized laboratories.

Tests – inspire/2010-01-13

SCHNEEBERGER Mineralgusstechnik s.r.o. Prumyslovy park 32/20 \* 350 02 Cheb – Dolni Dvory \* phone: +420 354 400 941 \* fax: +420 354 400 940 http://www.schneeberger.com

**Revision notice** 

Issue	Name	Author – date/initials	Checked	Approval
01	First issue	13.05.2010/QSU	01.06.2012 / HLA	26.05.2010 / HLA